

Обзор

Harness the power of focus

Keep presentations engaging with the Poly Studio E60 smart MPTZ optical zoom camera. The main presenter is always in frame, and every person in the room is shown with exceptional accuracy, even at the far end. With every detail captured, presentations are easier to follow.

Zoom in on all the details

Whether in person or remote, keep your teams engaged no matter where they're seated. Make sure they pick up on every detail with true-life definition including small gestures and expressions even in large rooms with a 12x optical zoom.

Distractions out. Engagement in

The Poly Studio E60 smart optical zoom camera lets everyone see what's going on in the room. Presenter tracking and Al-driven framing modes make sure the focus stays on the all-important action so nobody misses a beat, no matter where they are.

A simplified setup and easy to use

Kickstart meetings without delays and make every minute count with the Poly Studio E60 smart optical zoom camera. Its flexible connectivity and compatibility with top conferencing platforms simplifies things so you can solely focus on your presentation.

Making IT's job a little easier

Poly Lens, remote device management, gives you better visibility into workspaces across the entire organization. IT professionals can remotely monitor and troubleshoot Poly devices as well as streamline applying bulk software and policies[1].

Возможности

Keep the focus right where it belongs

Eyes for everyone. With a 12x optical zoom, the Poly Studio E60 smart MPTZ optical zoom camera can zero in on every detail and pick up content with amazing clarity, ensuring a deeper connection, and letting nothing escape its view.

Keep the presenter center-stage

Poly DirectorAl presenter tracking keeps the main speaker in focus during presentations, lessons, or speeches. It zooms in and follows them in real-time for a seamless, engaging virtual experience with minimal distractions.

Catch every detail in 4K

The ultra-HD imaging system and 4K sensors deliver stunningly detailed and sharp images for a visual experience that feels lifelike and true to reality, and makes virtual attendees feel more included and engaged.

In frame. In focus. Engaged

Keep all participants in-frame and engaged with Poly DirectorAl group framing. It smartly captures the entire group on screen, removing excess space and adjusting the angle for equal visibility. With everyone in frame, no one gets left out.

Just plug it in and you're on

IT will find the Poly Studio E60 smart MPTZ optical zoom camera easy to install on a monitor, wall, or ceiling. Its user-friendly setup allows for convenient and flexible connections, so anyone is ready to collaborate—even if they're not tech-savvy.

Works with your platform of choice

An IT manager's dream, the Poly Studio E60 smart MPTZ optical zoom camera was created for communication and is optimized and certified to work with top virtual meeting providers.

[1] Poly Lens software capabilities are limited to Poly devices and select HP cameras. For the most up to date list of supported devices you may check the support list here: https://info.lens.poly.com/docs/begin/supported-devices.

Дополнительные характеристики

Блок питания	External
Bec	1.79 kg
Вес в упаковке	3987 g
Вес паллеты	378 kg
Гарантия производителя	Poly standard one-year limited warranty
Горизонтальное поле зрения (hFoV)	71° (PTZ camera); 107° (panoramic camera)
Дальность действия камеры (метрическая система)	До 10 м
Диагональ поля обзора (dFoV)	78,1° (РТZ-камера)
Диапазон температур при эксплуатации	0 to 40°C
Длина кабеля	2 m
Защита на физическом уровне	Standard Kensington lock slot
Значение универсального кода продукции	198122304387
Картонных юробок в слое	4
Картонных юробок на паллете	20
Код UNSPSC	45121520
Комплект поставки	Ethernet cable; Wall mount kit; Quick start guide; Warranty card; Poly Studio E60; USB-B to USB Type-A cable
Минимальное количество для заказа	200
Минимальный размер (Ш x Г x B)	20 x 15 x 16.5 cm
Общее разрешение фотокамеры (мегапикселей)	2 x 8 MP
Паллета (уровни)	5
Порты	1 USB-B; 1 RJ-45 (10/100/1000 Mbps) Ethernet interface (supporting PoE+ power supply); AC/DC power jack
Программное обеспечение управления	Poly Lens Cloud
Продуктов в слое на паллете	16
Продуктов на паллете	80
Размеры упаковки (Ш x Г x B)	29.5 x 24.5 x 24.2 cm
Разрешение видео контента (входное)	UHD (3840 x 2160)

Разрешение видео людей	4K, 30 fps (TX and RX) from 2048 Kbps
Разрешение фотокамеры	2160p, 4K UHD (3840 x 2160)
Сертифицированное ПО для совместной работы	Zoom; Tencent
Сетевые возможности	1 10/100/1000 Mbps Ethernet supporting POE+/PSE
Совместимые операционные системы	Android; Windows
Страна происхождения	Made in China
Температура при хранении (Цельсия)	-40 to 70 °C
Техническое описание, фото 1	AHID/413b7f0db8d12f285299bc178d41329a6e5f10c2
Техническое описание, фото 2	AHID/e97833c16fa94fd2c168bce526272b9b3a694fc5
Техническое описание, фото 3	AHID/0fbb119c64092fb8c7fea03843de75dcde15d24e
Технология интеллектуальных камер	Group framing; Presenter tracking; Poly DirectorAl
Тип камеры	Dual-lens
Тип микрофона	Two-microphone element beamforming array
Тип фокуса	Auto focus
Трансфокатор	12x optical
Функции камеры	Motorized pan, tilt and zoom (MPTZ)
Функции крышки объектива	Attachable; Face away
Цвет	Black
Частота смены кадров	5–60 fps (up to 4K resolution at 15 fps in call)
Электропитание	AC/DC 12 V; Power over Ethernet (PoE+) injector ^[1]

[1] Sold separately.

Решения для гибридной модели работы

Voice
★ : Рекомендуемый

Аксессуары для конференц-телефонов

Блок питания Poly Trio C60 с кабелем питания и CAT-5

85X03AA

Видео

Видеоаксессуары

Монтажный кронштейн камеры Poly EagleEye IV

89L88AA

Отказ от ответственности — Авторские права

© HP Development Company, L.P., 2024. Информация в этом документе может быть изменена без предварительного уведомления. Гарантийные обязательства для продуктов и услуг HP приведены только в условиях гарантии, прилагаемых к каждому продукту и услуге. Никакие содержащиеся здесь сведения не могут рассматриваться как дополнение к этим условиям гарантии. HP не несет ответственности за технические, редакторские и иные ошибки в этом документе.

Generated by Dynamic Collateral Tool – (kz-ru) – Mar 26, 2024 7:58 AM UTC+0000